



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

MSI-BOC5 Breakout box

Description

The MSI-BOC5 is an interface box designed to breakout the signals from ETS 2-way CAT5 based speaker / microphone connections. It allows the use of a separate speaker and microphone with our SMAx-xxC5 products vs an ETS -C5 combination speaker/microphone.



Includes:

- MSI-BOC5 Breakout box
- Installation instructions.

Wiring requirements

CAT5 connection:

- HP devices 250 feet max
- MP devices 500 feet max
- LP devices 1000 feet max

Speaker: 22 gauge 2 conductor Shielded
25 feet max

Microphone: 22 gauge 2 conductor
Shielded 25 feet max

MSI-BOC5 Specifications

- Cat5/6 input connector
- Terminal blocks for speaker, microphone and call switch connections
- 70V 2.5W Speaker output.
ETS SM1 type or similar microphone input
- Call switch input
- Temperature range -40C to 85C.
- Black plastic ABS housing.
- Dimensions: L 3.3 x W 2.0 x H 1.6
- Weight .05lbs

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty 1 year parts and labor.

Made in USA