

Electronic Technical Services Inc. 211 Conchas SE

Albuquerque, NM 87123 PH 505-888-3923 FAX 505-888-3926 Website: www.etsnm.com Sound Surveillance tm

SMEA-1 PoE IP Camera Microphone Interface Box

Description

In line adaptor for tapping power off Ethernet powered IP cameras to supply power to ETS Sound Surveillance microphones and breakout box for terminating the microphone to the "microphone" or "line input" of IP cameras. Supports both modes A and B of IEEE802.3af.



Includes:

- SMEA-1 Interface
- One 6' 3.5mm patch cord
- Installation instructions.

Options:

 Add –RCA or –FL (Flying Leads) to P/N for alternate output cable.

Microphone wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 1000'

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

SMEA-1 Specifications

- RCA or 3.5mm audio output connector
- Microphone or line level output.
- Transformer isolated audio output.
- Adjustable audio output level.
- 3 position terminal block microphone input.
- RJ45 Ethernet in/out jacks
- Straight through CAT5 connections (no crossover)
- A/B mode switch for IEE802.3af power format.
- Internal regulator converts PoE 48-57Vdc to 15Vdc @ 10ma for powering one ETS microphone.
- Current consumption 15ma.
- Led power indicator
- PPTC fused.
- Operating Temperature –40C to 70C
- Dimensions: L 3.3 x W 2.0 x H 1.6
- Weight: .08kg

Warranty 1 year parts and labor.

Made in USA