



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SM6 Audio Surveillance Kit

Description

Complete single zone audio surveillance system. Can be used independently for monitoring live audio or with audio recorders or DVRs for recording and playback.



Kit Includes

- SM1 Pre-amplified microphone.
- SM1 Mounting screws
- SM3 Amplifier
- 15 Vdc 800ma AC adapter.
- 6' Dual RCA Patch cable.
- Warning label.

Wiring Requirements

- Stranded 22-gauge, 2-conductor shielded cable with drain wire.
Max. cable length: 1000'

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning label in plain view is all that is required.

Warranty

1 year parts and labor.

Made in U.S.A.

SM1 Microphone Specifications

- Omni-directional Electret element.
25' range in all directions.
- Frequency response: 350-12Khz.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Internal peak limiter circuit (.5 sec response)
- Adjustable gain.
- Hi/Lo volume range switch
- Hi and Low cut filter switches
- 3 position terminal block
- Flush mountable. Can also be mounted on a single gang electrical box.
- Power: 12-24VDC @ 10mA
- See SM1 data sheet for more information

SM3 Amplifier Specifications

- Standard RCA jacks for connection to audio recorders, DVRs, etc.
- 3 position terminal block microphone connection
- 3" full range speaker.
- Recorder monitor switch.
- 3.5mm Headphone jack.
- Power: 12-15 VDC @ 250mA.
- Reverse polarity protected and fused.
- Dimensions L 5.4 x W 4.1 x H 1.5
- See SM3 data sheet for more information.